



Safety swivel hoist rings
Drehbare Sicherheitsringschrauben
Uszy obrotowe transportowe

Max. load (P) Max. last (P) Max. DOR (P) In tones w tonach	Lifting type Hebeart Typ mocowania	Number of rings Anzahl der Ringe Ilość uszu	Lifting angle Hebe- winkel Kąt przy podno- szeniu	DSR			DSS			TSR			DSP			SEB																																			
				M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30	M36	M42	M48	M56	M8	M10	M12	M14	M16	M18	M20	M24	M30	M36	M42																						
		1	0°	0.3	0.6	1.0	1.3	1.6	2.0	2.5	3.0	4.0	5.0	6.3	6.3	10.0	10.0	12.5	15.0	20.0	20.0	25.0	32.1	32.1	32.1	32.1	0.3	0.6	1.0	1.6	2.5	4.0	5.0	6.3	10.0	12.5	20.0	22.0	0.3	0.6	1.0	1.3	1.6	2.0	2.5	1.6	2.5	4.0	6.3	10.0	12.5
		2	0°	0.6	1.2	2.0	2.6	3.2	4.0	5.0	6.0	8.0	10.0	12.6	12.6	20.0	20.0	25.0	30.0	40.0	40.0	50.0	64.2	64.2	64.2	64.2	1.2	2.0	3.2	5.0	8.0	10.0	12.6	20.0	25.0	40.0	44.0	0.6	1.2	2.0	2.6	3.2	4.0	5.0	3.2	5.0	8.0	12.6	20.0	25.0	
		1	90°	0.3	0.6	1.0	1.3	1.6	2.0	2.5	3.0	4.0	5.0	6.3	6.3	10.0	10.0	12.5	15.0	20.0	20.0	25.0	32.1	32.1	32.1	32.1	0.3	0.6	1.0	1.6	2.5	4.0	5.0	6.3	10.0	12.5	20.0	22.0	0.3	0.6	1.0	1.3	1.6	2.0	2.5	1.6	2.5	4.0	6.3	10.0	12.5
		2	90°	0.6	1.2	2.0	2.6	3.2	4.0	5.0	6.0	8.0	10.0	12.6	12.6	20.0	20.0	25.0	30.0	40.0	40.0	50.0	64.2	64.2	64.2	64.2	1.2	2.0	3.2	5.0	8.0	10.0	12.6	20.0	25.0	40.0	44.0	0.6	1.2	2.0	2.6	3.2	4.0	5.0	3.2	5.0	8.0	12.6	20.0	25.0	
		2	45°	0.4	0.8	1.4	1.8	2.2	2.8	3.5	4.2	5.6	7.0	8.8	8.8	14.0	14.0	17.5	21.0	28.0	28.0	35.0	44.9	44.9	44.9	44.9	0.8	1.4	2.2	3.5	5.6	7.0	8.8	14.0	17.5	28.0	30.8	0.4	0.8	1.4	1.8	2.2	2.8	3.5	2.2	3.5	5.6	8.8	14.0	17.5	
		2	60°	0.3	0.6	1.0	1.3	1.6	2.0	2.5	3.0	4.0	5.0	6.3	6.3	10.0	10.0	12.5	15.0	20.0	20.0	25.0	32.1	32.1	32.1	32.1	0.3	0.6	1.0	1.6	2.5	4.0	5.0	6.3	10.0	12.5	20.0	22.0	0.3	0.6	1.0	1.3	1.6	2.0	2.5	1.6	2.5	4.0	6.3	10.0	12.5
		4	45°	0.4	0.8	1.4	1.8	2.2	2.8	3.5	4.2	5.6	7.0	8.8	8.8	14.0	14.0	17.5	21.0	28.0	28.0	35.0	44.9	44.9	44.9	44.9	0.8	1.4	2.2	3.5	5.6	7.0	8.8	14.0	17.5	28.0	30.8	0.4	0.8	1.4	1.8	2.2	2.8	3.5	2.2	3.5	5.6	8.8	14.0	17.5	
		4	60°	0.3	0.6	1.0	1.3	1.6	2.0	2.5	3.0	4.0	5.0	6.3	6.3	10.0	10.0	12.5	15.0	20.0	20.0	25.0	32.1	32.1	32.1	32.1	0.3	0.6	1.0	1.6	2.5	4.0	5.0	6.3	10.0	12.5	20.0	22.0	0.3	0.6	1.0	1.3	1.6	2.0	2.5	1.6	2.5	4.0	6.3	10.0	12.5