# New Product

# HR-500 Trench Cover Swivel Hoist Rings









#### **Purpose**

✓ Provide a line of swivel hoist rings designed specifically to simplify the lifting and placement of steel covers used to cover trenches in streets and other traveled areas.





#### **Product Information**

#### ✓ RFID EQUIPPED

 Each trench cover comes "factory equipped" with an RFID chip for immediate utilization with various inspection and asset management software.







- ✓ Sizes available
  - WLL of 5000, 10000 & 15000 lbs.
- ✓ The Working Load Limit permanently stamped into each washer.



- ✓ All components are alloy steel
  - Quenched & Tempered.





- Multiple nuts are available to fit various thicknesses of cover steel.
  - 3/4", 7/8", 1", 1-1/4" & 1-1/2"





- ✓ HR-500 features a forged alloy steel bail that provides benefits you have come to expect from Crosby "forged" components.
  - More durable bail provides the increased toughness desired in potentially abusive filed conditions.
  - Easily readable "Raised Lettering" showing the name Crosby or "CG" and PIC Code for traceability.
  - Forged bail features larger throat opening than standard HR-125



- Design Factor of 5 to 1
- ✓ Rated at 100% of Working Load Limit at any angle.
  - 180 degree pivot and 360 degree swivel
- ✓ 100% individually Proof Tested to 2-1/2 times the Working Load Limit with certification.





#### **Product Information**

Each product has a Product Identification Code (PIC) for material traceability along with a Working Load Limit and the name Crosby or "CG" stamped into "load bearing components".





### **Product Information**

- ✓ Coil threads provide for quick rigging.
  - Fewer threads required than standard bolts
- Does not require any torque.



 Simply spin base down flush with work piece and tap one of the lugs with a hammer to tighten.



### **Product Information**

#### ✓ Trench Cover Accessories

Several "time saving" accessories are available with the HR-500 Trench Cover.





### **Product Information**

#### ✓ Trench Cover Accessories

- HR-500HG Thread No-Go Gauge
  - Separate tool for each Frame Size



IR-500H0 Thread No-Go Gauge



Aids in determining when studs and cover nuts need replacing.

If small end slides fully into nut, threads are worn and nut must be replaced.

If large end slides fully over threads, threads are worn and HR-500 must be replaced.



#### **Product Information**

- Trench Cover Accessories
  - HR-500TC Thread Clean Out Tool
    - Separate tool for each thread size



HR-500TC Thread Clean Out Tool

Aids in removing substances from threads, such as dirt, rock and mud, that could restrict proper installation of HR-500 Trench Cover.





#### **Product Information**

#### Trench Cover Accessories


- HR-500WF Welding Fixture
  - Separate tool for each thread size



HR-500WF Welding Fixture

Aids in the welding process by ensuring proper alignment of nut onto cover.

Fixture screws into nut, then rest on top of cover. Can be removed quickly once nut has been tack welded into position.






### **Product Application**

Like standard Crosby hoist rings, when installed properly, the base of the HR-500 must meet the load (work piece) surface.



**Work Piece** 

### **Product Application**



- Detailed warning and application instructions are shipped with each hoist ring.
  - Including welding guidelines

